

AVIRE FIRE COMMUNICATION SYSTEM

Product Datasheet

Optional Lift Intercom



CLEAR AND COMPLIANT LIFT COMMUNICATION FOR FIREFIGHTERS

The Optional Lift Intercom extends firefighter communication to additional locations beyond the fire service access level and machine room. Used as part of the AVIRE Fire Communication System, it enables compliant two-way communication with the lift car and all other optionally connected intercom units, providing flexibility for site-specific requirements.

System Features:

- Push-to-Talk, two-way communication with the lift car and all other intercom units
- Stainless-steel flush mount panel with steel mounting box
- Rated to IPX3
- System supports up to 8 optional lift intercoms
- Set-up via the AVIRE HUB

Specifications AC-DAV9-100-F-C0-EN1

Power Input	24VDC from the Fire Lift I/O unit
Operating Temperature	-20°C to 65°C
IP Rating	IPX3
Dimensions	220 x 110 x 39mm (intercom panel and flush mount box) 205 x 100 x 35mm (flush mount box)
Weight	519g (intercom panel); 317g (flush mount box)
Mounting	Flush Mount
Connection	4-Wire CAN
Maximum power consumption	2W
Screw type	Torx Tamper-proof screws

Ordering Information:

AC-DAV9-100-F-C0-EN1	Optional Lift Intercom Flush Mount
AC-MFV0-100-0-00-000	FIRE-FIGHTER: Lift Intercom Surface Mount Frame

Other AVIRE Fire Components:

AC-AMD0-200-F-C0-000	Fire Lift I/O Module
AC-FFL9-100-F-CP-EN1	Firefighters Lift Switch w/Pwr LED (EN)
AC-DAM9-100-F-CP-EN1	Machine Room Lift Intercom w/Picto Flush Mount

