

IP Command Center Base Station

2500-__RCV Series



IP Command Center Cabinet (Surface Mount)

Includes Phone & Distribution Module



Part #s:

- 10 Zone (2500-10RCV)
- 16 Zone (2500-16RCV)
- 32 Zone (2500-32RCV)
- 48 Zone (2500-48RCV)
- 64 Zone (2500-64XRCV)
- 80 Zone (2500-80XRCV)
- 96 Zone (2500-96XRCV)
- 112 Zone (2500-112XRCV)
- 128 Zone (2500-128XRCV)

Dimensions:

- **2500-10RCV, 16RCV** = 15.14" H x 12" W x 6.19" D
- **2500-32RCV, 48RCV, 64XRCV, 80XRCV, 96XRCV, 112XRCV, 128XRCV** = 21.03" H x 20.3" W x 5.19" D

Distribution Modules



10-48 Zone System



64-128 Zone System

- Install on a wall or table top
- Requires 120vac power with battery backup or RATH® RP7700104 power supply with battery backup
- Single dedicated phone line or IP phone system with our 2100-VOIP Interface

Dimensions:

10-48 Zone System: 2.04" H x 17.28" W x 11.8" D

64-128 Zone System: 6.83" H x 17.18" W x 8.9" D

Contact Us for Larger Projects

CODE COMPLIANCE:

- International Building Code (IBC)
- National Fire Protection Association (NFPA)
- Americans Disabilities Act (ADA)

PHONE CAPABILITIES:

- Calls wait in queue until previous call is disconnected and receive a message stating that an emergency call is in progress. When the prior call clears, the next phone in queue is connected.
- Includes handset and speaker phone for communication to Call Boxes
- Works with our model 2100 series IP Call Boxes. Connect back to Distribution Module via an Ethernet connection. Max 300' between network switches. IP Call Boxes require PoE at 802.3af.
- LEDs indicate which Call Boxes have initiated a call
- Rescue personnel can communicate with individual Call Boxes and outside party
- Audible alert sounds when Call Boxes place a call until Command Center joins conversation

Specifications:

Mounting: Surface

Design: Powder coated steel enclosure with twist lock closure

Warranty: 2 Years

POWER & WIRING REQUIREMENTS:

- Command Center and Sub-Master Stations are powered from PoE
- Command Center and Sub-Master Stations to Distribution Module: IP (PoE)

ADDITIONAL FEATURES:

- Can be configured with the main Command Center and multiple Sub-Master Stations (available in desk, surface, or flush mount)
- System requires an analog telephone line, an IP phone line when used with an IP Interface, or can be set up as an IP Intercom System