

PBX-M Phone

PBX-M



Part #: PBX-M

DESCRIPTION

This PBX-M Elevator Phone comes in a black powder coated metal finish designed to withstand harsh environments. It is also ADA compliant and made to fit into your elevator's phone cabinet. This phone has the reliability and features that you have come to expect from EMS products.

KEY FEATURES

- Phone line powered
- ADA compliant
- Phone line monitoring available
- On board keypad
- Optional on board relay
- Surface mount in a phone cabinet or wall
- Built in four number dialer
- Extended voice chip capability
- Easy installation and programming
- Fully programmable voice chip
- Available in one or two LED version
- Positive acknowledgement of alarm received
- Tone activated (not fooled by voicemail or other recordings)
- Voice prompts reduce operator error
- **Frequency Response:** 550Hz - 3400Hz, +/- 3db
- **Dialing:** DTMF (Dual Tone Multi Frequency)
- **Ring Sensitivity:** 40-120vac RMS
- **REN:** 0.2B
- **Optional AC adaptor:** 12vac @500mA
- **Industry Canada No.:** C22.2 No.60950-1-01, 2nd Ed
- **FCC Reg. No.:** US: NLFTE05B25668

Specifications:

Dimensions: 8.81" H x 4.62" W X 2.06" D

Weight: 3 lbs.

Power: Telephone line powered (48vdc to 50vdc typical)

Mounting: Surface mount

Loop Current Range: 10mA to 60mA (20mA typical)

Operating Current Range: 25mA to 55mA

Operating Temp: -40° - 185°F

Relative Humidity: Up to 95% (non-condensing)

Warranty: 2 Years