

Part #: PBX

## **DESCRIPTION**

The PBX elevator phone is fully ADA compliant and made to fit into your elevator's phone cabinet. This phone has the reliability and features that you have come to expect from EMS products.

## **KEY FEATURES**

- Phone line powered
- ADA compliant
- · Phone line monitoring available
- On board keypad
- Optional on board relay
- Surface mount in a phone cabinet or wall
- · Built in four number dialer
- · Extended voice chip capability
- · Easy installation and programming
- Fully programmable voice chip
- · Available in one or two LED version
- · Positive acknowledgement of alarm received
- Tone activated (not fooled by voicemail or other recordings)
- Voice prompts reduce operator error
- Frequency Response: 550Hz 3400Hz, +/- 3db
- Dialing: DTMF (Dual Tone Multi Frequency)
- Ring Sensitivity: 40-120vac RMS
- REN: 0.2B
- Optional AC adaptor: 12vdc@500mA
- Industry Canada No.: C22.2 No.60950-1-01, 2nd Ed
- FCC Reg. No.: US: NLFTE05B25668

## **Specifications:**

**Dimensions:** 1.73" W x 3.74" H

Weight: 3 ounces

Power: Requires 24vdc @ 500mA

Mounting: Behind the COP

Loop Current Range: 10mA to 60mA (20mA typical)

Operating Current Range: 18mA to 55mA

Operating Temp: -40° - 185°F

Relative Humidity: Up to 95% (non-condensing)

Warranty: 2 Years