

PSL Phone

PSL



KEY FEATURES

- Phone line powered
- ADA compliant
- Phone line monitoring available
- On board keypad
- Optional on board relay
- Mounts flush on the car panel
- Built in four number dialer
- Extended voice chip capability
- Easy installation and programming
- Fully programmable voice chip
- Available in one or two LED version
- Positive acknowledgement of alarm received
- **Frequency Response:** 550Hz - 3400Hz, +/- 3db
- **Dialing:** DTMF (Dual Tone Multi Frequency)
- **Ring Sensitivity:** 40-120vac RMS
- **REN:** 0.2B
- **Optional AC adaptor:** 12vdc@500mA
- **Industry Canada No.:** C22.2 No.60950-1-01, 2nd Ed
- **FCC Reg. No.:** US: NLFTE05B25668

Specifications:

Dimensions: 13-1/4" H x 10" W x 2-1/8" D

Weight: 4-1/2 lbs.

Power: Telephone line powered (48vdc to 50vdc typical)

Mounting: Flush mount

Loop Current Range: 10mA to 60mA (20mA typical)

Operating Current Range: 25mA to 55mA

Operating Temp: -40° - 185°F

Relative Humidity: Up to 95% (non-condensing)

Warranty: 2 Years