

Part #: PSM

DESCRIPTION

The PSM Phone is a surface mount low profile phone that is ADA compliant. It is phone line powered which eliminates the need to run a second pair of wires for power. Made of durable 16 gauge Stainless Steel, this unit can be used in elevators and hallways.

KEY FEATURES

- Phone line powered
- ADA compliant
- · Phone line monitoring available
- On board keypad
- · Optional on board relay
- · Mounts flush on the car panel
- · Built in four number dialer
- · Extended voice chip capability
- Easy installation and programming
- Fully programmable voice chip
- · Positive acknowledgement of alarm received
- Frequency Response: 550Hz 3400Hz, +/- 3db
- Dialing: DTMF (Dual Tone Multi Frequency)
- Ring Sensitivity: 40-120vac RMS
- REN: 0.2B
- Optional AC adaptor: 12vdc@500mA
- Industry Canada No.: C22.2 No.60950-1-01, 2nd Ed
- FCC Reg. No.: US: NLFTE05B25668

Specifications:

Dimensions: 9-1/2" H x 5-1/16" W x 1-3/8" D

Weight: 3-1/2 lbs.

Power: Telephone line powered (48vdc to 50vdc typical)

Mounting: Flush mount

Loop Current Range: 10mA to 60mA (20mA typical)

Operating Current Range: 25mA to 55mA

Operating Temp: -40° - 185°F

Relative Humidity: Up to 95% (non-condensing)

Warranty: 2 Years