

# SmartRescue System Call Box

2100-956RR



Part #: 2100-956RR

## CODE COMPLIANCE:

- International Building Code (IBC)
- National Fire Protection Association (NFPA)
- Americans Disabilities Act (ADA)
- ETL Listing Number: 5013373
- Conforms to UL Standard 2017 for Attendant Monitored Signaling Devices
- Complies with Section 6.4 of UL 60950-1

## POWER REQUIREMENTS:

- 24vdc from part # 2500-PWR24U

## PROGRAMMING FEATURES:

- Programmable with up to 5 emergency numbers
- Recordable location message (18 seconds)
- On-site keypad programming or remote programming

## PHONE CAPABILITIES:

- Requires analog telephone line (POTS, PBX, or central office line)
- Phone checks every 24 hours for an active phone line, if one is not detected, phone will provide a relay trip
- Automatic answer feature with audible ring
- Touch Tone operation only (Touch Tone is an AT&T registered trademark)

## Specifications:

**Dimensions:** 7-1/4" H x 4-3/4" W x 1-7/8" D

**Mounting:** Surface Mount

**Design:** Red Powder Coated

**Warranty:** 2 Years

## ADDITIONAL FEATURES:

- Compatible with SmartRescue Base Station or Command Center for in-building rescue coordination
- Built-in 10 phone consolidator feature allows you to install 10 Call Boxes and 1 Base Station on a single telephone line
- Remote or on-site diagnostic test
- Automatic dialer (31 digit programmable memory)
- Built-in battery backup recharges from 24vdc power (allows for a minimum of 4 hours of talk time upon power loss)
- 7.2V 300mAH battery (part # RP7300110)

### Optional Feature:

- Strobe interface and relay

# SmartRescue System

## Call Box

2100-956RR

