

SmartView Two-Way Elevator Visual Communication System

2100-SVE

RATH  **JANUS**
by AVIRE



CODE COMPLIANCE:

- Certified to CSA Standard B44.1, conforms to ASME Standard 17.5

POWER REQUIREMENTS:

- Injector Power: 56V-65W power adapter with dc jack included (120vac power cord).
- Requires backed up 120v source or RATH® RP7700104S.
- Extender Power: Supplies 1A to the SmartView Controller

WIRING REQUIREMENTS:

- **Extender Wiring:**
 - Extends up to 1,640 feet over single pair of wiring between extenders (requires single pair, 18-24ga, shielded or unshielded)
 - CAT5E with RJ45 connectors required from network switch and the SmartView Controller to each extender
 - Main Unit (Injector) has LAN In (internet connection) and LRP Out (two wire connection)
 - Remote Unit (Extender) has LRP In (two wire connection from main unit) and PoE Out (Ethernet connection to SmartView Controller)

FEATURES:

- Included RJ45 adapters for Interlink Cabling
- Supplies power and communication to the SmartView Controller

Specifications:

Dimensions: 1" H x 3.7" W x 2.75" D

Environmental: -49°F to 168°F (-45°C to 76°C)

Warranty: 2 Years



Ethernet Extenders

2100-SVE

