

Uninterruptible Power Supply Monitor

2500-UPSMONITOR



Part #: 2500-UPSMONITOR

POWER REQUIREMENTS:

24vdc @ 28mA / 24vac @ 69mA, 120vac @ 45mA / 230vac @ 36mA per module position

POLARIZED COIL INPUTS:

DC control inputs only

ENERGIZED INDICATOR:

One red LED per module position

CONTACT RATINGS:

Resistive load: 7A @ 30vdc, 10A @ 125vac, 7A @ 250vac
Inductive load: .25 HP 125/250vac (N.C.), .33HP 125/250vac (N.O.)

CONTACT CONSTRUCTION:

Dry form "C" DPDT per module position

AMBIENT TEMPERATURE:

32°F to 120°F (0°C to 49°C) @ 93% RH (@32°C) Non-Condensing / Non-Freezing

"/T" VERSIONS:

3.5" wide, low profile snap track provided with mounting screws

"/C" VERSIONS:

3.5" wide, low profile snap track provided with mounting screws

APPROVALS:

"T" versions: UL Recognized Component (UL864, UOXX2) File #S3403, CSFM File #7300-1004:106

"C" versions: UL Listed (UL864, UOXX), CUL Listed (UL864, UOXX7) File #S3403, CSFM File #7300-1004:101, MEA File #73-92-E Vol.14 (MR-101, MR-104), Vol.16 (MR-201, MR-204)

"C/R" versions: UL Listed (UL864, UOXX), CUL Listed (UL864, UOXX7) File #S3403, CSFM File

DIMENSIONS:

5-1/4" H x 3-1/8" W x 2-5/8" D