

2300-630RC

Command Center Machine Room Phone



Provides complete communication with a Command Center System.

- Acts as an additional location in a building for emergency responders to speak to a trapped elevator passenger.
- Wires directly into the Distribution Module alleviating the need for additional power or external phone lines.
- On-board keypad allows the user to select the desired elevator phone to call.
- Audible and visual call indicator for incoming calls.
- Fastens to any flat surface in a desired location.
- Multiple phones can be installed on one Command Center System providing more calling flexibility.



Specifications

Part Numbers	2300-630RC
Mounting	Surface Mount
Dimensions	8 1/2" H x 4" W x 4 1/2" D
Enclosure	Plastic
Weight	1.85 lbs
Communication	Analog
Power Source	Line powered from Distribution Module
Wiring Requirements	Single pair 22 AWG - 24 AWG from the Distribution Module
Environmental	32°F to 113°F
Warranty	2 years
Code Compliance	ASME standard A17.1, FCC part 15. UL listed.
Voltage	48 VDC
Included	2300-630RC phone with hardwired line cord, location chart
Site Requirements	Single pair 22 AWG - 24 AWG, RJ-11 wall plate

Supplemental Information

REN	0.5B
FCC Reg. No.	US: 6AHE05A19475

Compatible with the Following: RATH Command Center RATH SmartView Command Center



Rev Sep 25

AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089
800-451-1460 | sales.us@avire-global.com
avire-global.com/en-us