

3300 Call Boxes

SmartCommand Two-Way Communication (Area of Refuge)



Reliable emergency communication at every required location.

- Enables hands-free, two-way voice communication on all floors.
- Simple daisy-chain wiring for fast, efficient installation.
- Features braille label and a 1-inch+ emergency button.
- Easy text-to-speech programming via the central BOSS head unit.
- LED displays for power and active distress status.
- Optional protective cover available.



Specifications

	Flush Mount*	Surface Mount*	Exterior (NEMA) rated*
Part Number without Covering	3300FSN (Back Box RP7700504)	3300SS	3300S4
Part Number with Covering	3300FSCN	3300SSC	3300S4C
Dimensions	Faceplate: 8.66" H x 5.12" W x 0.48" D Cover: 7.83" H x 5.01" W x 0.59" D Backbox: 7.75" H x 3.77" W x 2.63" D	Faceplate: 7.78" H x 4.72" W x 2.21" D Cover: 7.83" H x 5.01" W x 0.59" D	Faceplate: 9.8" H x 6.3" W x 2.7" D Cover: 7.83" H x 5.01" W x 0.59" D
Material	Stainless steel Backbox: 18ga galvanized steel	Stainless steel	Stainless steel and fiberglass
Code Compliance	UL 2525, NFPA 72, 2022, NFPA 101, 2024, IBC/IFC 2024 & ADA		
Weight (Without Cover)	1.16 lb	1.99 lb	2.01 lb
Weight (With Cover)	1.2 lb	2.39 lb	2.05 lb
Wiring	Daisy-chained connection between call boxes with 18/4 CIC		
Connections	4 pin 5.08 mm pluggable terminal block		
Power	Powered by the BOSS unit Current draw: 48 VDC Typical idle: 0.44 W		
Sound	<70 dB		
Environmental	Temperature: 13°F – 131°F (10°C - 55°C), Humidity: <95%		
Warranty	2 years		

* Works with SmartCommand System: 3400 SmartCommand BOSS, 3200 SmartCommand Call Commander, and 1000 UPS Power Supply



Rev Sep 25

AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089
800-451-1460 | sales.us@avire-global.com
avire-global.com/en-us


Flush Mount Options



3300FSN



**3300FSCN
(with cover)**



RP7700504 Back Box
Required for Flush Mount
Call Boxes

Surface Mount Options



3300SS



**3300SS
(with cover)**

Exterior Surface Mount Options NEMA Rated



3300S4



**3300S4C
(with cover)**