

RP7700104S

Uninterruptible Power Supply (UPS)



Reliable battery backup for elevator communication systems.

- Can power up to 3 units with a 9Ah battery backup.
- Visual and audible alerts signal power loss.
- Provides 4 hours of talk time to meet ASME 17.1 code.
- Built-in surge protection safeguards connected equipment.



Specifications

Part Number(s)	RP7700104S
Mounting	Wall Mount (wall mount bracket included)
Dimension	11" H x 3.9" W x 14" D
Enclosure	Plastic
Weight	15 lbs.
Wiring Requirements	Connect via single pair
Environmental	32°F – 104°F
Warranty	2 years
Code Compliance	ASME 17.1, UL1778, cUL 107 5th, FCC DOC Class B
Input Voltage	120 VAC
Output Voltage	120 VAC
Compatible Equipment	SmartView 2, SmartView 1, In-Building Elevator Communication Systems



AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089
800-451-1460 | sales.us@avire-global.com
avire-global.com/en-us

Supplementary Info

Capacity	1000 VA / 600 W
Waveform	Simulated Sine Wave
Output	120 VAC \pm 5%
Plug Type & Cord	NEMA 5-15P, 6 ft. cord
Outlet Types	9 x NEMA 5-15R
Battery Quantity	1
Battery Size	12 V / 9 Ah
Battery Type	Sealed Lead-Acid Battery
Additional Compliance	RoHS
Certification	Energy Star



AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089
800-451-1460 | sales.us@avire-global.com
avire-global.com/en-us