

# RP7701500 Uninterruptible Power Supply (UPS)

Analog Command Center Two-Way Communication (Area of Refuge)



## Maintains system functionality during power loss.

- Automatic Voltage Regulation (AVR) technology ensures stable AC power supply.
- 24 hours battery back-up power under quiescent load conditions and an additional 60 minutes full functionality.
- Multifunction rotatable LCD provides utility and battery backup status.
- Visual and audible alarm indicators.
- Surge only outlet for connection to UPS.
- Supports the Command Center's analog setup up to 116 call boxes.



## Specifications

Dimensions	3.5" H x 17" W x 18.8" D
Battery Weight	59.5 lbs
Container Material	Black metal
Input	<b>Voltage:</b> 90 VAC to 140 VAC <b>Frequency Range:</b> 47 Hz to 63 Hz <b>Plug type:</b> NEMA 5 - 15 P <b>Plug style:</b> Straight <b>Cord length:</b> 10 ft
Output	<b>VA:</b> 1,500 <b>Watts:</b> 1,125 <b>Automatic voltage requirements:</b> Yes <b>On battery voltage:</b> 120 VAC $\pm$ 5% <b>On battery frequency:</b> 60 Hz $\pm$ 1% <b>On battery waveform:</b> Simulated Sine Wave <b>Outlet type:</b> NEMA 5 - 15R <b>Outlet batteries &amp; surge protectors:</b> 8 <b>Overload protection:</b> Internal circuitry limiting / circuit breaker <b>Transfer time:</b> 4 ms
Battery	<b>Battery type:</b> Sealed Lead-Acid <b>Battery size:</b> 12 V / 7 Ah <b>User replaceable:</b> Yes <b>Typical recharge time:</b> 8 hours
Surge Protection & Filtering	<b>Surge suppression:</b> 1,840 J <b>Coax protection RG6:</b> 1-In, 1-Out <b>Phone protection RJ11:</b> 1-In, 1-Out (combo)



Rev Sep 25

# AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089  
800-451-1460 | sales.us@avire-global.com  
avire-global.com/en-us

## Specifications

Management and Communication	<b>LCD interface displays:</b> Load/current level, Runtime, Battery level, Temperature (F & C), Battery in use, Input voltage, Output voltage, Output frequency, Overload, Wiring Fault, Battery shutdown voltage, Static frequency Tolerance, Slew rate, Silent mode, Normal mode <b>HID compliant USB port:</b> Yes <b>Serial port:</b> Yes (2x) <b>Management cable:</b> USB, Serial (2) <b>LED indicators:</b> Power on, Wiring fault <b>Audible alarms:</b> On battery, Low battery, Overload
Environmental	<b>Operating temperature:</b> 32°F to 104°F (0°C to 40°C) <b>Operating humidity:</b> 0% to 90% (non-condensing)
Warranty	2 years
Certifications	<b>Safety:</b> UL1778, cUL 107.3, FCC DOC Class B <b>Environmental:</b> RoHS Compliant

Compatible with Analog Command Center.



Rev Sep 25

# AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089  
 800-451-1460 | [sales.us@avire-global.com](mailto:sales.us@avire-global.com)  
[avire-global.com/en-us](http://avire-global.com/en-us)