SHW / SHW-MR

Master Station for EMS5 Call Director



Centralized communication from lobby and machine room locations.

- Enables building-wide communication when paired with JANUS EMS5.
- Audible alert and display show incoming call location.
- · Connects elevator devices with internal or external parties.
- · Keypad allows direct calls to the elevator car.
- Functions as an intercom-only system for 24/7 on-site monitoring.
- · Installs quickly with no additional programming.



Specifications

	Lobby Master Station	Machine Room Master Station
Part Numbers	SHW	SHW-MR
Mounting	Surface Mount* Surface Mount*	
Dimensions	9-3/16" W x 9-3/16" H x 5" D 9-3/16" W x 9-3/16" H x 5" D	
Enclosure	Powder-Coated Metal	Powder-Coated Metal
Weight	6 lbs.	6 lbs.
Communication	Analog Analog	
Power Source	110 VAC	110 VAC
Wiring Requirements	Single pair 20-22 ga to EMS5 Single pair 20-22 ga to EMS5	
Environmental	32°F - 122°F 32°F - 122°F	
Warranty	2 years	2 years
Code Compliance	ASME A17.1 / CSA B44, IBC, FCC, ISED, and ADA. CSA listed. ASME A17.1 / CSA B44, IBC, FCC ISED, and ADA. CSA listed.	
Voltage	12 VDC	12 VDC
Included	SHW, Plug-in 12 VDC transformer, Biscuit jacks, Line cords	SHW-MR, Plug-in 12 VDC transformer, Biscuit jacks, Line cords
Optional Equipment	Elevator communication failure systems	Elevator communication failure systems
Site Requirements	110 VAC power, 20-22 gauge twisted pair wiring 110 VAC power, 20-22 gauge twisted pair wirin	

^{*} Can be modified to desk mount by adding part number: SDK.



Supplemental Information		
REN	0.2 B	
Industry Canada No.	C22.2 No.60950-1-07, 2nd Ed	
FCC Reg. No.	US: NFLTE02B33770	

Electrical	
Included AC Adapter	110 VAC to 12 VDC @ 500 mA
Operating Current Range	25 mA to 55 mA

Compatible with the Following Systems: JANUS EMS5