

2400-805 Exterior Rated Call Boxes

Analog Command Center Two-Way Communication (Area of Refuge)



Simple two-way communication for rescue assistance.

- Single home run wire for each call box enables easy, cost-effective installation.
- Location message provides site-specific call identification.
- Triggered alert when line loss is detected.
- Call button and LED call indicator.
- Scalable, reliable, and compliant solution connects directly to an addressable fire alarm module or panel, adhering to all industry standards.



Specifications

Part Numbers	2400-805LP	2400-805LPC1
Dimensions	7-1/4" H x 4-3/4" W x 1-7/8" D	Face Plate: 10" H x 6-17/25" W Back Box: 9-7/8" H x 6-1/2" W x 3" D Cover: 9-3/4" H x 6-1/2" W x 1-1/4" D
Enclosure	NEMA 4 Rated Red Fiberglass	NEMA 4 Rated Red Fiberglass with Cover
Mounting	Surface Mount	
Weight	6.6 lbs	
Wiring Requirement	1 pair 22 AWG to 24 AWG	
Maximum Wiring Distances	6,200 ft for 22 AWG and 3,900 ft for 24 AWG	
Programming	On-site programming, Recordable location message (25 seconds)	
Phone Capabilities	Automatic answer feature with audible ring	
Supervision	Can be obtained with addition of Supervisory Module (2500_SPRVSR)	
Power Source	Distribution module	
Electrical	Hardwired transformer: 24 VAC / 5 VA @ 120 VAC / 60 Hz source Battery (supplied): 7.2 VDC @ min 1.3 Ah	
Environmental	32°F to 120°F	
Warranty	2 years	
Code Compliance	IBC, NFPA 72, ADA	

Compatible with the Following: RATH Command Center



Rev Nov 25

AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089
800-451-1460 | sales.us@avire-global.com
avire-global.com/en-us

2400-805LP and 2400-805LPC1

