

2500-VOIPM IP SUPERVISOR

IP Command Center Two-Way Communication (Area of Refuge)



Compliant supervision for communication pathway integrity.

- Monitors up to 200 RATH IP endpoints (phones and POE Command Centers).
- Performs automatic system checks every 10 minutes (adjustable).
- Sends contact closure alarms if an endpoint is unreachable or the network fails.
- Each device has a unique IP address that the 2500-VOIPM pings to confirm it's connected.
- Provides power failure alerts via relay output when combined with the UPS Monitor (2500-UPSMONITOR).



Specifications

Part Numbers	2500-VOIPM
Dimensions	4.3" H x 8.3" W x 2.6" D
Mounting	Wall Mount Enclosure with Door
Weight	21 lbs
Power Requirements	120 VAC from a backed up power source or RATH RP7700104
Current Draw	270 mA
Output	(2) Form 1C SPDT switches, (1) NO and (1) NC. Rated 277 VAC at 20 A
Ethernet	(2) 10 Base-T or 100 Base-T, 8-pin RJ45 connection
Network	Ethernet IPv4 Requires static IP addresses for all components Supports web browser: HTTP/HTTPS, XML, Modbus/TCP & SNMP protocols
LED Indicators	Green (power on) Yellow (network)
Additional Feature	Non-volatile memory
Environmental	32°F to 120°F
Warranty	2 years
Code Compliance	IBC, NFPA 72, ADA, Electromagnetic compliance: IEC CISPR 22, 24 FCC 47CFR15 (Class B) UL 61010-1
Works with	Command Center IP, 2100-VoIP2CS



Rev Sep 25

AVIRE

N56 W24720 N. Corporate Circle Sussex, WI 53089
800-451-1460 | sales.us@avire-global.com
avire-global.com/en-us