

SHW / SHW-MR

Call Director System Master Station



Centralized communication for elevator monitoring and response.

- Provides machine room communication for one or two elevators.
- Shares a single phone line between elevator phone and intercom.
- Simple in/out connections for quick installation without complex wiring.
- Compact design mounts easily to flat surfaces in the machine room.
- Compliant with ADA, ASME A17.1 / CSA B44, and IBC requirements.



Specifications

	SHW	SHW-MR
Function	Lobby Master Station	Machine Room Master Station
Mounting	Surface*	
Dimensions	9.1875" x 9.1875" x 5.0"	
Enclosure	Powder-Coated Metal	
Weight	6 lbs.	
Communication	Analog	
Power Source	110 VAC	
Wiring Requirements	Single Pair 20 - 22-gauge to EMS5	
Environmental	32 - 122°F	
Warranty	2 Years	
Voltage	12 VDC	
Included Components	SHW or SHW-MR, Plug-In 12 VDC Transformer, Biscuit Jacks, Line Cords	
Site Requirements	110 VAC Power, 20 - 22-gauge Twisted Pair Wiring	
Compatible JANUS® Products	EMS5	

* Can be modified to desk mount by adding part number: SDK

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com

avire-global.com/en-us

Supplementary Information

REN	0.2 B
Industry Canada No.	C22.2 No.60950-1-07, 2nd Ed
FCC Reg. No	US: NFLTE02B33770
Electrical	
Included AC Adapter	110 - 12 VDC @ 500 mA
Operating Current Range	25 - 55 mA