

# 2300-630SM

SmartRescue System Machine Room Phone



## Direct communication between responders and elevator passengers.

- Provides an additional communication point for emergency responders.
- Connects directly to the SmartRescue System without external power or phone lines.
- On-board keypad allows users to call specific elevator phones.
- Visual and audible indicators alert users to incoming calls.
- Surface-mount design allows flexible installation locations.
- Compliant with ASME A17.1 and FCC requirements. UL listed.



## Specifications

<b>Mounting</b>	Surface	<b>Environmental</b>	32 - 113°F
<b>Dimensions</b>	8.5" x 4.0" x 4.5"	<b>Warranty</b>	2 Years
<b>Enclosure</b>	Plastic	<b>Voltage</b>	48 VDC
<b>Weight</b>	1.85 lbs	<b>Included Components</b>	2300-630RC Phone with Hardwired Line Cord, Location Chart
<b>Communication</b>	Analog	<b>Site Requirements</b>	Two Pair 22 - 24 AWG, RJ-11 Wall Plate
<b>Power Source</b>	Line Powered from SmartRescue	<b>REN</b>	0.5 B
<b>Wiring Requirements</b>	Two Pair 22 - 24 AWG from SmartRescue	<b>FCC Reg. No.</b>	US: 6AHTe05A19475
<b>Compatible RATH® Products</b>	RATH® SmartRescue, RATH® SmartView SmartRescue		

# AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089  
800-451-1460

sales.us@avire-global.com

[avire-global.com/en-us](http://avire-global.com/en-us)