


66125

2 Hour Fire-Rated Cable 18-8 AWG Solid Bare Copper



Fire-rated cable for critical voice and data communications.

- Maintains critical communication circuits during fire conditions.
- 2-hour fire-rated construction for life safety applications.
- Shielded 4-pair cable supports voice and data communication.
- Meets NFPA 72 Level 2 and Level 3 survivability requirements.
- Rated for wet-location installations and outdoor exposure.



Specifications

| | |
|----------------------------|--|
| Length | 500 ft. |
| Weight | 63.0 lbs / 126.0 lbs per kft |
| Nominal Diameter | 0.504" |
| Temperature | 194°F (90°C) |
| Conductor | 18-8 AWG Solid Bare Copper |
| Cabling | 4 Pairs |
| Insulation | Low Smoke, Zero Halogen Thermoset Fire-Roc® |
| Jacket | Red Non-Halogen Flame Retardant Polyolefin (Sequential Footage Markers Every 2 ft) |
| Shield | Copper (Shielded Constructions Only) |
| Tape | Flame Retardant Tape |
| Drain | 1-8 AWG Stranded Bare Copper (Shielded Constructions Only) |
| Nominal Capacitance | 18 pF/ft |
| Volts | 660 V |

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com

avire-global.com/en-us