


AV000015, AV000016

2 Hour Fire-Rated Cable 18-4 AWG Solid Bare Copper



Fire-rated cable for critical life safety communications.

- Maintains critical communication circuits during fire conditions.
- 2-hour fire-rated construction for life safety applications.
- 2-pair cable supports voice and data communication.
- Meets NFPA 72 survivability requirements.
- Suitable for use with RATH® Addressable SmartCommand System.



Specifications

	AV000015	AV000016
Length	500 ft	1,000 ft
Conductor	18-4 AWG Solid Bare Copper	
Cabling	2 Pairs	
Insulation	Fire-Resistive, Low-Smoke	
Jacket	Red Fire-Resistive Flame-Retardant	
Shield	Copper	
Drain	Drain Wire Provided In Shielded Construction	
Conductor Colors	May Be Supplied In Either All Black Or Black & Red Configurations	
Conductor Markings	Individual Conductor Identification	
2-Hour Fire Resistance	ANSI/UL 2196	
Volts	600 V	

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com
avire-global.com/en-us



This cable may be sourced from a range of approved suppliers, including Marmon 36512, Radix CTS18A0104, and Belden 5322FME. While markings, certifications, and certain physical construction details may differ, all approved options provide the required 18 AWG 4 conductor construction and UL 2196 fire-resistive performance for use with the SmartCommand system. When an approved equivalent cable is used, there is no functional difference in SmartCommand system capability or in meeting the applicable code requirements. Approved equivalents are certified to UL 2196 and suitable for NFPA 72 survivability requirement

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com

avire-global.com/en-us