


AV000017, AV000018

2 Hour Fire-Rated Cable 18-2 AWG Solid Bare Copper



Fire-rated cable for critical emergency communication systems.

- Maintains critical communication circuits during fire conditions.
- 2-hour fire-rated construction for life safety applications.
- Available for installation with or without conduit.
- Meets NFPA 72 survivability requirements.
- Suitable for use with RATH® Analog SmartRescue and Command Center Systems.



Specifications

	AV000017	AV000018
Length	500 ft	1,000 ft
Conductor	18-2 AWG Solid Bare Copper	
Cabling	2 Conductors, Twisted	
Insulation	Fire-Resistive, Low-Smoke	
Jacket	Red Fire-Resistive Flame-Retardant	
Shield	Copper	
Drain	Drain Wire Provided In Shielded Construction	
Conductor Colors	Typically Supplied In Black & Red Configurations	
Conductor Markings	Individual Conductor Identification	
2-Hour Fire Resistance	ANSI/UL 2196	
Volts	300 V	

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

avire-global.com/en-us



This cable may be sourced from a range of approved suppliers, including Marmon 36397, Radix CTS18A0102, and Belden 5320FME. While markings, certifications, and certain physical construction details may differ, all approved options provide the required 18 AWG 4 conductor construction and UL 2196 fire-resistive performance for use with the SmartCommand system. When an approved equivalent cable is used, there is no functional difference in SmartCommand system capability or in meeting the applicable code requirements. Approved equivalents are certified to UL 2196 and suitable for NFPA 72 survivability requirement.

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com

avire-global.com/en-us