

RP7500094

Communication Cable 22-2 AWG Plenum-Rated



Reliable plenum-rated cable for critical systems.

- Designed for critical communication systems.
- Bare copper construction supports reliable signal transmission.
- 2-pair cable supports voice and data communication.
- Shielded construction helps reduce signal interference.
- CMP-rated for plenum installation environments.



Specifications

Length	1,000 ft
Weight	20 lbs
Nominal Diameter	0.194"
Temperature	32 - 167°F (0 - 75°C)
Conductor	22-2 AWG Solid Bare Copper
Cabling	2 Pairs
Insulation	Low-Smoke PVC 0.008"
Jacket	Blue Low-Smoke PVC 0.018"
Marking	SMARTWIRE Device / Zone A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US
Shield	Aluminum Mylar
Drain Wire	24 AWG 7 Strand Tinned Copper
Nominal Capacitance	51 pF/ft
Signal Speed	37 Ohms
Volts	300 V
Flame Rating	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
Compliance	NEC Article 800 UL Listed C(UL)US CMP RoHS

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

avire-global.com/en-us