


# RP7500094B

Communication Cable 18-4 AWG Plenum-Rated



## Reliable plenum-rated cable for critical communication systems.

- Designed for advanced addressable communication systems.
- Solid bare copper conductors support reliable signal transmission.
- Shielded cable construction helps reduce signal interference.
- Sequential footage markings simplify installation and measurement.
- Suitable for two-way communication and area of refuge systems.



## Specifications

<b>Length</b>	1,000 ft
<b>Weight</b>	33 lbs
<b>Nominal Diameter</b>	0.159"
<b>Temperature</b>	-4 - 167°F (-20 - 75°C)
<b>Conductor</b>	18-4 AWG Solid Bare Copper
<b>Cable</b>	4 Conductors @ 5" LHL
<b>Insulation</b>	Plenum PVC
<b>Color Code</b>	Black, Red, Yellow, Blue
<b>Ripcord</b>	Located Under Jacket
<b>Jacket</b>	Red Plenum PVC
<b>Jacket Print</b>	COMTRAN 18 AWG FPLP/CL3P (UL) OR CMP C(UL)US RoHS (01-12345) 000002 (01-12345) = Traceability Code Sequential Footage Markings Every 2 ft
<b>Mutual Capacitance</b>	24 pF/ft Nominal @ 1 KHz
<b>DC Resistance</b>	6.7 Ω/1000 FT Nominal @ 68°F (20°C)

# AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

[avire-global.com/en-us](http://avire-global.com/en-us)

<b>Compliance</b>	
<b>UL</b>	C(UL)US Listed Type CMP UL Listed Type FPLP/CL3P UL Subject 444 Communications Cables UL1424, Power Limited Fire Alarm Cab
<b>NFPA</b>	262 (UL 910), Plenum Flame Test
<b>NEC</b>	Article 760 Article 725 Article 800
<b>State Fire Marshal</b>	California Approved
<b>CSA</b>	UL Type FPLP/CMP/CL3P
<b>Other</b>	RoHS