

2500-SPRVSR

Analog Command Center System Supervisory Module



Continuous supervision for critical emergency communication pathways.

- Monitors remote call boxes and phone lines.
- Detects communication failures and triggers an alert.
- Relay output integrates with fire alarm systems.
- Connects directly to each 2400 Series call box.
- Available for systems with up to 116 zones.
- Provides NFPA 72 (2016) 360° supervision



Specifications

	2500-12SPRVSR	500-16SPRVSR	2500-36SPRVSR	2500-56SPRVSR	2500-116SPRVSR
Zones	12	16	36	56	116
Dimensions	3.5" x 19.25" x 6"		7.0" x 19.25" x 6"	10.5" x 19.25" x 6"	
Mounting	Wall-Mounted Swing-Out Bracket				
Connections	RJ11 to call boxes and phone lines; punch-down terminals to Distribution Module				
Power Requirements	12 VDC; includes UL-listed transformer for 120 VAC source				
Alternative Power	RATH® RP7700104, RP7701500, or 2500-PWRUPS				
Monitoring	Remote call boxes and phone lines; relay output triggered when a component is not detected				
UPS Monitor	2500-UPSMONITOR included unless otherwise specified				
Warranty	2 Years				

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

avire-global.com/en-us