

# 2500-UPSMONITOR

Analog Command Center System Power Supervisory Module



## Continuous power supervision for Analog Command Center systems.

- Monitors power throughout the communication system.
- Detects power loss and triggers a relay output.
- Red LED provides visual status indication.
- Dry contacts support integration with external systems.
- Compact design provides flexible mounting options.
- Supports NFPA 72 360° supervision requirements.



## Specifications

|                          |                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------|
| Dimensions               | 5.25" H × 3.125" W × 2.625" D                                                           |
| Power Requirements       | 24 VDC @ 28 mA; 24 VAC @ 69 mA; 120 VAC @ 45 mA;<br>230 VAC @ 36 mA per module          |
| Control Input            | Polarized coil input (DC control only)                                                  |
| Status Indicator         | One red LED per module position                                                         |
| Contact Type             | Dry Form C, DPDT per module position                                                    |
| Resistive Contact Rating | 7 A @ 30 VDC; 10 A @ 125 VAC; 7 A @ 250 VAC                                             |
| Inductive Contact Rating | 0.25 HP (N.C.); 0.33 HP (N.O.) @ 125/250 VAC                                            |
| Operating Temperature    | 32°F to 120°F                                                                           |
| Humidity                 | Up to 93% RH, non-condensing and non-freezing                                           |
| Mounting Options         | /T: 3.50" snap track with screws<br>/C: 18 ga CRS back box with 0.50" conduit knockouts |

## Approvals

|      |                                                                 |
|------|-----------------------------------------------------------------|
| /T   | UL Recognized Component (UL 864, UOXX2), CSFM                   |
| /C   | UL Listed (UL 864, UOXX), CUL Listed (UL 864, UOXX7), CSFM, MEA |
| /C/R | UL Listed (UL 864, UOXX), CUL Listed (UL 864, UOXX7), CSFM, MEA |

# AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

[sales.us@avire-global.com](mailto:sales.us@avire-global.com)

[avire-global.com/en-us](http://avire-global.com/en-us)