

2100-ALARM-S/SV

Elevator Communications Failure Surface Mount System



Continuous monitoring for elevator emergency communication systems.

- Monitors elevator emergency phone lines for communication failures.
- Audible and visual alarms notify personnel of phone line loss.
- Monitors up to 10 JANUS® 2100 Series elevator phones.
- Key switch silences alarms for up to 24 hours or until service is restored.
- Available in horizontal and vertical surface mount configurations.
- Compliant with ASME A17.1, CSA B44, and UL requirements.



Specifications

	2100-ALARM-S	2100-ALARM-SV
Orientation	Horizontal	Vertical
Dimensions	3.75" H × 6.75" W × 3.67" D	6.75" H × 3.75" W × 3.67" D
Mounting	Surface Mount	
Enclosure	Stainless steel	
Weight	1.43 lbs	
Input Power	24 VAC/VDC	
Wiring	Single pair, 22–24 AWG	
Operating Temperature	32°F to 120°F	
Included Components	Alarm board, junction board, reset key switch, LED, and reset keys	
Optional Accessories	Backup power and power supply options	
Warranty	2 Years	

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com
avire-global.com/en-us