

LMA / LMA-NC

Elevator Communications Failure Line Monitoring Alert



Continuous monitoring for elevator emergency communication systems.

- Monitors elevator emergency phone lines for communication failures.
- Audible and visual alarms notify personnel of phone line loss.
- Verifies end-to-end communication.
- Key switch silences alarms during service.
- Available in flush mount or behind-the-panel configurations.
- Compliant with ASME A17.1 and CSA B44 requirements.



Specifications

	LMA	LMA-NC
Mounting	Flush Mount	Behind-the-Panel
Dimensions	Faceplate: 10.5" H x 5" W Backbox: 10.5" H x 4" W x 3" D	3.13" H x 3.70" W x 0.97" D
Enclosure	Stainless Steel	None
Weight	4.0 lbs	2.0 lbs
Included Components	LMA board, enclosure, reset key switch, LED, two 2111 reset keys, 12 VDC plug-in transformer	LMA board, LED, standoff kit, 12 VDC plug-in transformer
Power Source	110 VAC or 12–24 VDC	
Wiring	Single pair, 18–24 AWG	
Operating Temperature	32°F to 158°F	
Optional Accessories	Backup power options	
Warranty	2 Years	

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com
avire-global.com/en-us