

2100-956SIP/C2

IP Command Center System Surface Mount Call Box



Network-based emergency communication for IP Command Center systems.

- VoIP provides clear network-based communication.
- Dials up to five programmable emergency numbers.
- Recordable location message identifies the caller's location.
- Line supervision detects communication loss.
- Available with or without a protective cover.
- Compliant with IBC, NFPA 72, and ADA requirements.



Specifications

	2100-956SIP	2100-956SIPC2
Protective Cover	No	Yes
Enclosure	Stainless Steel	Stainless Steel with Protective Cover
Faceplate Dimensions	9.00" H × 5.92" W × 2.35" D	10.00" H × 6.68" W
Back Box Dimensions	-	9.875" H × 6.50" W × 2.30" D
Cover Dimensions	-	9.75" H × 6.50" W × 1.25" D
Weight	2.25 lbs	2.75 lbs
Mounting	Surface Mount	
Wiring	Cat3 or Better	
Max. Wiring Distance	300 ft Between Network Switches	
Programming	On-Site; Up to 5 Emergency Numbers	
Location Message	18 Seconds, Recordable	
Dialer	Automatic; 31-Digit Programmable Memory	
Answering	Automatic Answer with Audible Ring	
Supervision	Optional RATH® 2500-VOIPM	
Power Requirement	PoE 802.3af with Battery Backup	
Operating Temperature	32°F to 120°F	
Warranty	2 Years	

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

avire-global.com/en-us