

2100-958 Series

IP Command Center System Flush Mount Call Box



Integrated IP emergency communication for flush mount applications.

- VoIP provides clear network-based communication.
- Dials up to five programmable emergency numbers.
- Recordable location message identifies the caller's location.
- Triggered alert indicates detected line loss.
- Multiple finishes and protective cover options available.
- Compliant with IBC, NFPA 72, and ADA requirements.



Specifications

	2100-958NSIP	2100-958NMBIP	2100-958SIPC2
Protective Cover	No	No	Yes
Enclosure	Brushed Stainless Steel	Antique Bronze	Brushed Stainless Steel
Faceplate Dimensions	9.5" x 7.5"	9.5" x 7.5"	11.375" x 8.0"
Back Box Dimensions	8.0" x 6.0" x 3.0"	8.0" x 6.0" x 3.0"	9.875" x 6.5" x 3.0"
Cover Dimensions	-	-	9.75" x 6.5" x 1.25"
Weight	7.0 lbs	7.0 lbs	7.5 lbs
Mounting	Flush Mount		
Wiring	Cat3 or Better		
Max. Wiring Distance	300 ft Between Network Switches		
Programming	On-Site; Up to 5 Emergency Numbers		
Location Message	18 Seconds, Recordable		
Dialer	Automatic; 31-Digit Programmable Memory		
Answering	Automatic Answer with Audible Ring		
Supervision	Optional RATH® 2500-VOIPM		
Power Requirement	PoE 802.3af with Battery Backup		
Operating Temperature	32°F to 120°F		
Warranty	2 Years		

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

avire-global.com/en-us