

2500-VOIPM

IP Command Center System IP Supervisory Module



Continuous network supervision for IP emergency communication systems.

- Monitors up to 200 RATH® IP endpoints.
- Automatically checks system connectivity every 10 minutes.
- Detects unreachable devices and network failures.
- Relay outputs provide notification of supervision faults.
- Supports power supervision with the 2500-UPSMONITOR.
- Compliant with IBC, NFPA 72, ADA, FCC, and UL 61010-1 requirements.



Specifications

Mounting	Wall Mount Enclosure with Door
Dimensions	11.50" H × 10.00" W × 5.00" D
Weight	21 lbs
Power Requirements	120 VAC from Backed-Up Power Source or RATH® RP7700104
Current Draw	270 mA
Outputs	(2) Form 1C SPDT; (1) NO and (1) NC; 277 VAC @ 20 A
Ethernet	(2) 10 Base-T or 100 Base-T, 8-Pin RJ45
Network	Ethernet IPv4
IP Requirements	Static IP Address Required for All Components
Supported Protocols	HTTP/HTTPS, XML, Modbus/TCP, SNMP
System Capacity	Up to 200 IP Endpoints
Supervision Interval	10 Minutes, Adjustable
LED Indicators	Green: Power; Yellow: Network
Memory	Non-Volatile
Operating Temperature	32°F to 120°F
Warranty	2 Years

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089
800-451-1460

sales.us@avire-global.com
avire-global.com/en-us