

3200D / 3200F / 3200S

Addressable SmartCommand System **Call Commander**



Centralized emergency call management for SmartCommand systems.

- Displays and manages emergency calls from a central location.
- Supports communication with individual call boxes or all call boxes.
- Large display prioritizes active calls by location and urgency.
- Centralized programming simplifies system configuration.
- Compatible with all SmartCommand BOSS controllers.
- Compliant with UL 2525, NFPA 72, NFPA 101, IBC, IFC, and ADA requirements.



Specifications

	3200D	3200F	3200S
Mounting	Desk Mount	Flush Mount	Surface Mount
Dimensions	7.95" × 9.84" × 3.03"	16.11" × 14.0" × 3.0"	15.14" × 12.0" × 6.19"
Weight	2.57 lbs	20.35 lbs	20.0 lbs
Enclosure	N/A	Powder-coated steel with twist-lock closure	
Communication	Hands-free speaker, microphone, and control buttons		
Display	LCD monitoring panel		
Power Source	SmartCommand BOSS Controller		
Power Consumption	Idle: 5.4 W • Active: 8.16 W		
Wiring	18 AWG two-wire pairs (Part # RP7500094B) or 2-hour fire-rated cable (Part # 66120) where required		
Connections	4-pin 5.08 mm pluggable terminal block		
Sound Level	<70 dB		
Operating Environment	23°F to 131°F (-5°C to 55°C), 5–95% RH		
Warranty	2 Years		

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

avire-global.com/en-us

7.29.2026