

3300FSN / 3300FSCN

Addressable SmartCommand System Emergency Call Box



Flush mount emergency communication for a clean, integrated installation.

- Hands-free, two-way voice communication.
- Flush mount design blends into finished walls.
- Daisy-chain wiring reduces installation time and wiring costs.
- Centralized programming through the SmartCommand BOSS controller.
- Optional protective cover available.
- Compliant with UL 2525, NFPA 72, NFPA 101, IBC, IFC, and ADA requirements.



Specifications

	3300FSN	3300FSCN
Protective Cover	No	Yes
Weight	1.16 lbs	1.20 lbs
Required Back Box	RP7700504	RP7700504
Cover Dimensions	—	7.83" × 5.01" × 0.59"
Faceplate Dimensions	8.66" × 5.12" × 0.48"	
Back Box Dimensions	7.75" × 3.77" × 2.63"	
Faceplate Material	Stainless Steel	
Back Box Material	18 ga Galvanized Steel	
Wiring	Daisy-chain using 18/4 CIC cable	
Connections	4-pin 5.08 mm pluggable terminal block	
Power	Powered by SmartCommand BOSS controller	
Operating Environment	13°F to 131°F (-10°C to 55°C), <95% RH	
Warranty	2 Years	
Power Consumption	Idle: 0.52 W • Active: 0.67 W	
Sound Level	<70 dB	

AVIRE

N56W24720 N Corporate Cir., Sussex, WI 53089

800-451-1460

sales.us@avire-global.com

avire-global.com/en-us